







BASIC - FISSA - PRO

salamandre / finishing ovens



SALAMANDRA PRO 1/1 G



Potenza
Power
Spannung
Puisseance

Alimentazione
Power source
Betriebsspannung
Alimentation

Zone riscaldanti
Heating areas
Heizzeiten
Zones chauffant

Dimensioni interne
Internal dimensions
Innenmaße
Dimensions intérieures

Dimensioni vano cottura
Cooking compartment dim.
Oberfläche
Dimensions module de cuisson

Peso netto
Net weight
Nettogewicht
Poids net

Dimensioni imballo
Shipping
Verpack. abmessungen
Dim. emballage

Peso lordo
Gross weight
Bruttogewicht
Poids brut

	Watt	n.	mm	mm	mm	mm	mm	mm	mm	mm	mm	Kg	mm	kg
Salamandra BASIC	2800	230V 50/60 Hz F+N	1	480x330 h.320	-	620	350	445	430	-	-	16	670x450x480	18
Salamandra FISSA	2800	230V 50/60 Hz F+N	1	480x330 h.320	-	620	350	445	430	-	-	18,5	670x450x480	20,5
Salamandra PRO 1/2 G	1700	230V 50/60 Hz F+N	1	-	385x350	330	400	400	545	510	30	45	500x630x650	50
Salamandra PRO 1/1 G	3400	230V 50/60 Hz F+N	2	-	585x350	510	400	600	545	510	30	56	750x630x630	66

Potencia
Potência
Мощность

Alimentação
Alimentação
Электропитание

Zonas calentadoras
Zonas de aquecimento
Зоны нагрева

Dimensiones internas
Dimensões internas
Внутренние размеры

Dimensiones del espacio de cocción
Dimensões espaço de cozimento
Размеры зоны выпекания

A B C D E F G

Peso neto
Peso líquido
Вес нетто

Dimensiones embalaje
Dimensões embalagem
Размеры упаковки

Peso bruto
Peso bruto
Вес брутто



SALAMANDRA PRO 1/2 G



SALAMANDRA FISSA - BASIC