



THE ONE



H 505TS

H 509TS

H 512TS

H 517TS

H 524TS

		H505TS	H509TS	H512TS	H517TS	H524TS
Dimensioni Esterne	Larghezza [mm]	790	790	790	790	1.100
	Profondità [mm]	735	835	835	835	1.065
	Altezza [mm]	850	1.320	1.800	1.950	1.800
Luce Porta	Larghezza [mm]	670	670	670	670	670
	Altezza [mm]	380	630	830	1.110	830
Profondità Interna Utile [mm]		410	420	420	420	900
Classe Climatica		T	T	T	T	T
Capacità Abbattimento in 90'	+90 > +3°C [Kg]	18	25	36	55	72
Capacità Congelamento in 240'	+90 > -18°C [Kg]	12	16	24	36	48
Tipo Teglie - Griglie		GN1/1 600x400	GN1/1 600x400	GN1/1 600x400	GN1/1 600x400	GN2/1 600x800
Capacità Teglie	Passo [mm]	6	12	17	23	17
	Passo [mm]	5	9	12	17	12
	Passo [mm]	4	7	10	14	10
Dati Elettrici	Alimentazione Elettrica [V / ~ / HZ]	230 / 1 / 50	230 / 1 / 50	400 / 3 / 50	400 / 3 / 50	400 / 3 / 50
	Potenza in Riscaldamento [W]	500	1.000	1.600	1.600	1.600
	* Potenza Frigorifera [W]	1.430	2.108	4.807	7.061	9.986
	** MAX Assorbimento Elettrico in Raffreddamento [W / A]	1.117 / 5,5	1.395 / 6,1	3.218 / 7,4	4.507 / 9,2	5.837 / 12,9
	MAX Assorbimento Elettrico in Riscaldamento [W / A]	625 / 2,7	1.105 / 4,8	1.780 / 7,8	1.855 / 8,1	1.910 / 8,3

* T. Evap.= -15°C / T.cond.= +40°C / ** T.evap.= -15°C / T. Cond.= +55°C